



Safety Data Sheet

Issue Date: 06-Sep-2011

Revision Date: 20-Jan-2015

Version 1

1. IDENTIFICATION

Product Identifier

Product Name PC-7, Part B

Other means of identification

SDS # 130519-20B

Recommended use of the chemical and restrictions on use

Recommended Use Multi-purpose epoxy paste.

Details of the supplier of the safety data sheet

Supplier Address

Protective Coatings Co.
221 S Third St.
Allentown, PA 18102 USA

Emergency Telephone Number

Company Phone Number 610-432-3543 / 800-220-2103
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Black paste

Physical State Paste

Odor Slight amine

Classification

This chemical does not meet the hazardous criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). However, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

Unknown Acute Toxicity

85-95% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Talc	14807-96-6	10-30
Kaolin	1332-58-7	15-30
Titanium Dioxide	13463-67-7	1-5
Ceramic Fiber	142844-00-6	1-5
Carbon Black	1333-86-4	1-5

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

* Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). (Titanium Dioxide, Ceramic Fiber and Carbon black) Inhalation of particulates unlikely due to product's physical state.

4. FIRST-AID MEASURES

First Aid Measures

General Advice	Provide this SDS to medical personnel for treatment. After first aid, get appropriate in-plant, paramedic, or community medical support.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If eye irritation persists: Get medical advice/attention.
Skin Contact	Wash with soap and water. Remove and wash contaminated clothing before reuse. Get medical attention if irritation occurs.
Inhalation	Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician / poison center if individual's condition declines or if symptoms persist.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Seek medical advice.

Most important symptoms and effects

Symptoms	Moderate skin and eye irritation. Direct contact may cause temporary redness and discomfort. May cause discomfort if swallowed.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Skin and eye conditions may be aggravated by long term exposure.
---------------------------	--

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, CO2 or water spray.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Product is not flammable.

Hazardous Combustion Products Carbon monoxide. Carbon dioxide (CO2). Aldehydes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Wear positive pressure self-contained breathing apparatus (SCBA). Do not release runoff from fire control methods to sewers or waterways. NFPA Class IIIB.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

- Personal Precautions** Wear protective gloves/protective clothing and eye/face protection. Remove any contaminated clothing and wash thoroughly before reuse.
- Environmental Precautions** See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

- Methods for Containment** Prevent further leakage or spillage if safe to do so.
- Methods for Clean-Up** Dispose of contents/container to an approved waste disposal plant.

7. HANDLING AND STORAGE**Precautions for safe handling**

- Advice on Safe Handling** Handle in accordance with good industrial hygiene and safety practice. Wear appropriate personal protective equipment. Do not eat, drink or smoke when using this product. Wash face, hands, and any exposed skin thoroughly after handling.

Conditions for safe storage, including any incompatibilities

- Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Store contents under <90F (32C) . NFPA Class IIIB storage.
- Incompatible Materials** No information available.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Kaolin 1332-58-7	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Talc 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	(vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust
Carbon Black 1333-86-4	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
Titanium Dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³

Ceramic Fiber 142844-00-6	TWA: 0.2 fiber/cm ³ respirable fibers: length >5 μm, aspect ratio >=3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination	-	-
------------------------------	---	---	---

Other Information

If product is sanded, appropriate respirator should be worn to avoid breathing dust. Pre-existing respiratory disorders may be aggravated by exposure. If sanded, this material may generate silica / titanium dust. Inhaled silica / titanium has been classified by IARC as a human carcinogen (see section 11).

Appropriate engineering controls

Engineering Controls

Provide general or local exhaust ventilation if product is sanded or ground.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Chemical safety goggles/faceshield.

Skin and Body Protection

Wear protective gloves and protective clothing.

Respiratory Protection

Ensure adequate ventilation, especially in confined areas. If engineering controls do not keep airborne concentrations below acceptable levels, wear a NIOSH-approved respirator.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Paste	Odor	Slight amine
Appearance	Black paste	Odor Threshold	Not determined
Color	Black		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	> / = 2.0 - < / = 12.0	
Melting Point/Freezing Point	Not available	
Boiling Point/Boiling Range	No data	
Flash Point	110 °C / 230 °F	CC (closed cup)
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	Not determined	
Upper Flammability Limits	Not available	
Lower Flammability Limit	Not available	
Vapor Pressure	Not determined	
Vapor Density	Not available	
Specific Gravity	0.86	(1=Water)
Water Solubility	Insoluble in water	
Solubility in other solvents	Alcohols	
Partition Coefficient	Not determined	
Auto-ignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	
Density	7.2 lbs/gal	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Excessive heat over long periods of time.

Incompatible Materials

No information available.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact	May cause moderate eye irritation.
Skin Contact	Prolonged contact may cause redness and irritation.
Inhalation	Under normal conditions of intended use, this material is not expected to be an inhalation hazard.
Ingestion	May cause discomfort if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Aliphatic Polyaminoamide 68410-23-1	>2000 mg/kg (rat)	2000 mg/kg (rat)	-
Hydrocarbon Resin 9003-53-6	>1000 mg/kg (mice)	-	-
Carbon Black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
Titanium Dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen. However, the product as a whole has not been tested. Carbon black is a possible carcinogen when it appears as a respirable dust. Titanium dioxide is a possible carcinogen when it appears as a respirable dust. Ceramic Fiber is a possible carcinogen when it appears as a respirable dust.

Chemical Name	ACGIH	IARC	NTP	OSHA
Talc 14807-96-6		Group 3		
Hydrocarbon Resin 9003-53-6		Group 3		
Carbon Black 1333-86-4	A3	Group 2B		X
Titanium Dioxide 13463-67-7		Group 2B		X
Ceramic Fiber 142844-00-6	A2	Group 2B	Reasonably Anticipated	X

Legend**ACGIH (American Conference of Governmental Industrial Hygienists)**

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Numerical measures of toxicity

Not determined

Unknown Acute Toxicity

85-95% of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION**Ecotoxicity**

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Talc 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static		
Carbon Black 1333-86-4				5600: 24 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Not determined

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

- Disposal of Wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.
- Contaminated Packaging** Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. TRANSPORT INFORMATION

- Note** Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.
- DOT** Not regulated
- IATA** Not regulated
- IMDG** Not regulated

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Talc	Present	X		Present		Present	X	Present	X	X
Kaolin	Present	X		Present		Present	X	Present	X	X
Titanium Dioxide	Present	X		Present		Present	X	Present	X	X
Ceramic Fiber							X	Present		
Carbon Black	Present	X		Present	Present	Present	X	Present	X	X

Legend:

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List*
- EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*
- ENCS - Japan Existing and New Chemical Substances*
- IECSC - China Inventory of Existing Chemical Substances*
- KECL - Korean Existing and Evaluated Chemical Substances*
- PICCS - Philippines Inventory of Chemicals and Chemical Substances*
- AICS - Australian Inventory of Chemical Substances*

US Federal Regulations

SARA 313
Not determined

US State Regulations

California Proposition 65
This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Carbon Black - 1333-86-4	Carcinogen
Titanium Dioxide - 13463-67-7	Carcinogen
Ceramic Fiber - 142844-00-6	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Talc 14807-96-6	X	X	X
Kaolin 1332-58-7	X	X	X
Carbon Black 1333-86-4	X	X	X
Titanium Dioxide 13463-67-7	X	X	X
Ceramic Fiber 142844-00-6	X		

16. OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability	Special Hazards
	1	1	0	Not determined
HMIS	Health Hazards	Flammability	Physical Hazards	Personal Protection
	1	1	0	B- Safety Glasses, Gloves

Issue Date: 06-Sep-2011
 Revision Date: 20-Jan-2015
 Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet